VITARA



24" Dual Zone Wine Cooler VBWC5202D Panel Ready



Features

- Built Under or Free Standing installation
- Energy Class: DOE
- True integrated installation
- 4.7 CuFt & 52 Bottles capacity
- Dual Temperature zones Upper 35° F(2° C) -50° F(10° C) - Bottom 50° F(10° C) - 68° F(20° C)
- Interior air fan circulating
- Charcoal filter
- 5 wooden shelves with full extension slide-out roller

- Three adjustable LED lighting (white, blue, amber)
- Low-E, two layer anti-UV resistant glass door
 Electronic touch control with white Led Readout
- Sabbath mode
- Open door alarm
- Door reversible
- Hettich hinge
- Customized wooden panel or SS external panel (Sold Separately

Model	Lock	Finish	Description
VBWC5202D	No	Panel Ready	24" Dual Zone Wine Cooler Panel Ready

Model Details

Dimensions/Weight	Detail
Product Depth	22 3/8"
Product Height	34 1/8"
Product Width	23 1/16"
Product Weight	101 lbs

Dimensions/Weight	Detail
Product Volume	4.7 Cubic Feet
Shipping Dimensions	W26" X D24 5/8" X H37 3/16
Shipping Weight	108 lbs



www.vitaraamerica.com | 1.800.299.3406 MG Home Solution LLC

100 Illinois Street, Suite 200, St Charles, IL 60174


Integration/Panel Information*	Detail
Panel Height	34 ³ ⁄16
Panel Thickness	3/4"
Panel Width	23 11/16
Maximum Panel Weight	22 lbs


Electrical	Detail
Electrical Requirements	110V/60Hz
Volt Range	104V - 127V
Electrical Service	15 Amps
Running Amps	0.7 Amps
Approvals/Certifications	Detail
ETL Residential/Commercial	Yes


Model	Detail
Control Type	Electronic Touch Controls
Indoor or Outdoor	Indoor
Built-in Installation	Built in or Free Standing
Refrigerant Type	R600a


Capacities	Detail
12 oz Can Capacity	
25 oz Bottle Capacity	52 Bottles (Bordeaux style)


Installation Instructions












Installation Clearance Requirements

When installing the beverage cooler under a counter, follow the recommended spacing dimensions shown.

- For proper clearance of the electrical plug, allow at least 1" of clearance at the back as shown in the diagram.
- An installation next to a wall will require a minimum 2-1/4" door clearance to accommodate the handle.
- The cabinet should allow at least 24" for the width and 34-1/4" for the height to accommodate the beverage cooler.
- The power cable is located on the back right of the unit and has a length of 72" to accommodate multiple outlet locations.
- Once you are ready to install the unit, you must adjust the feet to level the beverage cooler.
- The installation should allow the unit to be pulled forward for servicing, if necessary.







www.vitaraamerica.com | 1.800.299.3406 MG Home Solution LLC

100 Illinois Street, Suite 200, St Charles, IL 60174